

Declaration of Performance

No.

CAN – EU13 – 1234; 4321; 2314*

(*one only of the listed mill numbers will appear in the grade stamp on the timber)

Unique identification (code) of the product type:

S-P-F WPCE

Strength-graded structural timber with rectangular cross-section in accordance with NLGA National Grading Rule for Dimension Lumber + EU Export Annex,

dry-graded (KD in the grade mark)

Cross-section dimensions (mm) **38 x 64; 89; 114; 140; 184; 235; 286**

with eased edges not exceeding 3 mm and in accordance with EN 336 Tolerance Class 2

Intended uses:

For use in buildings and bridges

Manufacturer:

Company Name
Address

System of AVCP: 2+

Notified Factory Production Control Certification Body
BM TRADA Certification Limited - No. 1224

Declared Performance

Essential characteristics	Performance	Harmonised Technical Specification
Modulus of elasticity (mean), bending, compression, tension and shear strengths (EN 338 + EN 1912)	C16/C20/C24 <i>as per the grade stamp</i>	EN 14081-1: 2005 + A1: 2011
Reaction to fire	D-s2, d0	
Biological durability – natural WPCE Spruce-Pine-Fir (S-P-F)	EN 350-2 Durability Class 5 sapwood not specifically excluded	
Release of dangerous substances	none used	

The performance of the product identified above is in conformity with this declared performance.

This Declaration of Performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the producer identified above.

Signed for and on behalf of the producer by:

.....
(name and function)

.....
(place and date of issue)

.....
(signature)